



**TENDER FOR  
PROVISION OF SMALL WORKS:  
REPAIR OF POTHOLES**

**TENDER SC 380/2008**

**COMPANY/PERSON:** \_\_\_\_\_

**ADDRESS:** \_\_\_\_\_  
\_\_\_\_\_

**TELEPHONE NUMBER:** \_\_\_\_\_

**FAX NUMBER:** \_\_\_\_\_

**DATE:** \_\_\_\_\_

**TENDER:**

**REPAIR OF POTHOLES:**

☐

**SIGNATURE:** \_\_\_\_\_

**CONTACT PERSON:** \_\_\_\_\_

**MOBILE PHONE NUMBER:** \_\_\_\_\_

TENDER FOR THE PROVISION OF SMALL WORKS SCHEDULE OF WORKS		
SECTION 1: PRELIMINARY AND GENERAL		
ITEM	CLAUSE	DESCRIPTION
1.	1200 A	<p>The rates shall include:</p> <p>All fixed charge obligations including all contractual requirements, insurance, facilities for the contractor, site establishment and removal and all time related charge obligations, including supervision, overheads and other obligations.</p> <p>Contractor must show proof that he/she is registered at</p> <p>(1) U.I.F (2) Workman's Compensation Commissioner (3) SETA</p>

**OVERSTRAND MUNICIPALITY**

## SCHEDULE OF QUANTITIES

**Repair of Potholes**

ITEM	CLAUSE	DESCRIPTION	UNIT	HER
2.1		Holes 0.0 to 30.0mm deep. Medium graded cold or hot premix on 65% cat emulsion at 1.2 l/m <sup>2</sup>	m <sup>2</sup>	
2.2		Holes 0.0 to 150 mm deep. Fill 120mm with base coarse material and compact to the satisfaction of the Town Engineer. <i>(Holes to be chipped out squarely to the correct depth. Fill top 30mm as in item 1)</i>	m <sup>2</sup>	
		SLURRY		
2.3.		Conventional type: 6-12 mm thick, 1 % cement content	m <sup>2</sup>	
2.4		Quickset: 6-12 mm thick 1.5 - 2.0 % cement content	m <sup>2</sup>	